



Multi-ply #1 Hip using steel plates for ply to ply connections




 $\frac{\text{Multi-ply TSC3.00 or TSC4.00 \#1 Hip using}}{\text{TTC7 clips for ply to ply connections}}$ 



Multi-ply TSC2.75 #1 Hip using TTC5 or TTC7 for ply to ply connections

(A) = ASTM A653 SS Grade 33 G60 steel plate on each face Bare Metal Thickness = 0.0329" (.83mm)



Steel Plate (Typ.)
Placed within 1" (25mm) of each supported truss to girder connection

## Plate Dimensions:

X = 3.5"(89mm) for 2-ply TSC2.75 #1 Hip X = 6.0"(152mm) for 2-ply TSC3.00 #1 Hip X = 6.0"(152mm) for 2-ply TSC4.00 #1 Hip X = 5.0"(127mm) for 3-ply TSC2.75 #1 Hip X = 8.0"(203mm) for 3-ply TSC3.00 #1 Hip X = 8.0"(203mm) for 3-ply TSC4.00 #1 Hip

## General Notes:

- Attachment of supported trusses to #1 Hip must be per TS025 or TS025A. Reference these TrusSteel Standard Details for allowable supported truss reactions, uplifts and connection requirements.
- 2. The top and bottom chords of all trusses shall be properly connected to structural sheathing or purlins.
- 3. All edge distances, end distance and spacing are 9/16" (14mm) minimum.
- 4. Circled numbers represent quantity of #10 self-drilling tapping screws per clip.
- 5. Truss must be analyzed with concentrated loads directly in line with correctly placed girder vertical webs. Reference details TS025 & TS025A for correct web placement information.
- 6. Clips/plate pairs must be placed within 1" (25mm) of each supported truss to girder connection.
- 7. Refer to approved truss drawings for other connections between plies.
- 8. Cold—Formed Steel Calculations are per the 2010 supplement to the AISI 2007 "North American Specifications for the Design of Cold—Formed Steel Structural Members" (S100—07/S2—10).

## TrusSteel®

www.TrusSteel.com

Florida: 1950 Marley Drive / Haines City, FL 33844 / (800) 755-6001 Missouri: 13389 Lakefront Drive / Earth City, MO 63045 / (800) 326-4102

## Multi-ply #1 Hips -

Ply To Ply Connection Detail

ITW Building Components Group, Inc. shall not be responsible for any performance failure in a connection due to a deviation from this detail. Any variation from this detail shall be approved in advance by ITW Building Components Group, Inc.

Standard Detail:

TS025D

Date:

07/16/12

TrusSteel Detail Category:

Ply-to-Ply Connections